

## BIO ALL PURPOSE VARNISH

<b>DESCRIPTION</b>	A transparent varnish in gloss or satin providing a colourless, hard but flexible dirt- and water-repellent finish. Sweat and saliva proof. For use on all interior timber surfaces, such as windows, banisters, furniture, toys, ceilings and panels. Not recommended for constantly humid environments such as bathrooms and laundries. Note: for timber flooring see BIO Floor Varnish
<b>PREPARATION</b>	Wood should be well sanded, dry and cleaned of greasy, waxy and dirty contaminants using <u>BIO Thinner</u> . Hardwoods and timbers rich in natural oils, waxes, acids and terpenes should be degreased using Bio Thinner, because these substances may mix with the varnish and prolong its drying time. Let dry for 24 hours. Old coats must be removed.
<b>PRIMING</b>	Baltic Pine and Pinus Radiata: Prime with one coat of Priming Oil. Remove excess oil after 15-30 minutes. Allow to dry for 24 hours, then apply BIO All Purpose Varnish.
<b>APPLICATION</b>	Stir thoroughly before use with a broad flat stirrer. Thin with 10-20% <u>BIO Thinner</u> to obtain a smooth flowing consistency. Brush thinly and evenly, working varnish well into the grain. Thick coats wrinkle when dry. Avoid bubbles. Allow 12 to 24 hours to dry between coats. Lightly sand between coats if necessary with fine sandpaper. Apply the second and subsequent coats only after the previous coat has thoroughly dried. Low temperature and humid conditions prolong the drying time. Do not paint below +10C and or above 80% humidity or in cold damp conditions, or when condensation, rain, dew or frost are likely to occur. Provide adequate ventilation during application and drying. Reaches maximum durability after 21 days.
<b>INGREDIENTS</b>	Based on tung oil, pine resins, wax, essential oils, paraffin oil, quartz, bentone, lead free drying agents.
<b>CLEANING</b>	Use BIO Thinner.
<b>COVERAGE</b>	1 Litre covers 15-18 sqm., depending on the absorbency of the timber.
<b>PACKAGING</b>	1Litre and 4 Litres
<b>PRECAUTION</b>	Flammable liquid. Keep away from open flames and out of the reach of children. Please dispose used rags in a sealed metal container. Can spontaneously combust.
<b>STORAGE</b>	Keep tightly sealed in a cool and dry place. Surface film may develop in opened cans.



20/05/2005

Going Solar  
60 Leicester St  
Carlton VIC 3053  
T 03 9348 1000  
F 03 9348 0077  
retail@goingsolar.com.au  
www.goingsolar.com.au

The preceding information is given as a general guide only. Some variations may occur or be advisable for particular conditions. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.

**BIO ALL PURPOSE VARNISH is an environmental friendly product.**