

BIO ENAMEL LACQUER UNDERCOAT AND INTERIOR

DESCRIPTION	Bio Enamel Lacquer is a thick, dirt-repellent and water-repellent, gloss or satin painted finish, containing no toxic solvents, resins or heavy metals. Suitable for all wood types, steel, aluminium and copper. Especially suitable for use on toys, panelling, skirtings and architraves, garage doors and window frames. Bio Enamel Lacquer satin is suitable for interior use only. Bio Enamel Lacquer Gloss is suitable for interior and exterior use.
PREPARATION	Prepare the surface in accordance Australian Standard 2311 Painting of Buildings. Surfaces should be well-sanded, dry and cleaned of greasy, waxy and dirty contaminants using <u>BIO Thinner</u> . Hardwoods and other timbers rich in natural oils, waxes, acids and terpenes should be degreased using Bio Thinner because these substances may mix with the paint and prolong its drying time. Old coatings must be removed. Timber moisture content must be under 15% for softwood, and under 12% for hardwood.
METAL PRIMING	Provides anti-corrosive protection for steel, aluminium, brass and copper. Not effective on zinc and galvanised surfaces. The metal should be cleaned of all grease, dirt, processing soil, salt residues, weld scale, rust and other residue which is likely to affect the performance of a protective coating. Apply 2 coats of Metal Primer thinly and evenly. Lightly sand between coats when completely dry. Finish with one coat of Bio Enamel Lacquer Undercoat and two coats BIO Enamel Lacquer white or coloured.
APPLICATION	Stir thoroughly before use with a broad flat stirrer. Thin as desired with 5-10% <u>BIO Thinner</u> to obtain a smooth flowing consistency. Apply one coat of BIO Enamel Lacquer Undercoat and two coats of BIO Enamel Lacquer white or coloured. Minimum dry film thickness is 100 microns.
DRYING	Apply second and subsequent coats only after previous coat has thoroughly dried. This will take between 24 and 40 hours, and longer with cold or damp weather. Do not be tempted to apply paint too thickly, as this retards the drying process. Lightly sand if necessary after the undercoat. Do not use below +10C and above 80% humidity or in cold damp conditions, or when condensation, rain, dew or frost are likely to occur. Provide adequate ventilation during application and drying. Reaches maximum durability after 8-14 days. When used on floors, furniture may be brought in with due care after three days.
COLOURS	Bio Enamel Lacquer and Undercoat are supplied in base white. Standard full colours are: Green, Blue, Ochre, Yellow, Brown, Red & Black All colours can be used as tints. The customer tints to his/her own satisfaction. All colours are intermixable/ Note: slight variations between lots are possible.

INGREDIENTS	Based on Castor oil, pine resin, tung oil, tall oil, lemon peel oil, paraffin oil, lecithin, bentone, ethanol, lead free drying agent, talc, feldspar, iron oxide, metal and mineral pigments. Free of cadmium, chromates and lead.
CLEANING	Use BIO Thinner.
COVERAGE	1 Litre covers 10-12 sqm., depending on the absorbency of the substrate.
PACKAGING	White and Undercoat : 250ml, 1 and 5 Litres Colours 250 ml, 1 and 2.5 Litres
PRECAUTION	Keep away from open flames and out of the reach of children. Please dispose used rags in a sealed metal container. Can spontaneously combust.
STORAGE	Keep tightly sealed in a cool and dry place. Surface skin may develop in opened cans.
DESCRIPTION	A highly concentrated cleaner for the toughest jobs in the house. It can be used to clean all ceramic surfaces like basis, bathtubs and toilets as well as stainless steel surfaces.
APPLICATION	Toilet: Spread evenly. Allow working for several minutes. Remove stubborn stains with a brush, then flush. All other surfaces: Spread evenly and wipe off with a cloth. Rinse with clear water.
INGREDIENTS	Water, lavender oil, lemon oil, ethanol, citric acid, chlorophyll, potash, formic acid, amphoteric and anionic detergents from coconut, polysaccharide. 99% bio degradable according to OECD Test.
PACKAGING	500 ml and 20Litres
STORAGE	Store in a cool, frost-free place. Close bottle well after use. Keep out of the reach of children.

PRECAUTION

**keep out of reach of children. Following eye and skin contact:
Rinse for an adequate length with water.**

The preceding information is given as a general guide only. Some variations may occur or be advisable for particular conditions. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.

BIO ENAMEL LACQUER is an environmental friendly product