

BIO ANTIQUE WAX & HARD FLOOR WAX

DESCRIPTION	Transparent, matt-finished sealing waxes without synthetic additives BIO waxes seal the pores and form a durable, anti-static surface that repels water and dirt. For use on all types of wood surfaces as an alternative to lacquer or varnish, especially on new and antique furniture, toys, shelves etc. BIO Hard Floor Wax may be used on all types of timber floor surfaces, stone, tile or slate. Not recommended for use where moisture or condensation occur.
PREPARATION	Wood and other surfaces should be well sanded, dry and cleaned of greasy, waxy and dirty contaminants using <u>BIO Thinner</u> . Old coatings must be removed. Prime, if necessary with Bio Priming Oil or Bio Teak Oil. Hardwoods and other timbers rich in natural oils, waxes, acids and terpenes should be degreased using Bio Thinner because these substances may mix with the oils and waxes and prolong their drying time
APPLICATION	BIO Antique Wax and BIO Hard Floor Wax are ready-to-use. It might be helpful especially during cold weather to soften the wax by standing the container in a 60 +C water-bath. Apply thinly and evenly with a lint free cloth or brush, working the wax well into the grain. Thick coats may cause white streaks. Polish after 3-5 hours.- do not leave until completely dry as buffing is then very difficult. On stone, tile or slate thin BIO Hard Floor Wax with 50% of BIO Thinner. Depending on wear and tear, apply a new thin coat of wax every 4 to 6 months. Provide adequate ventilation during application and drying.
MAINTENANCE	Wipe treated surfaces with a cloth moistened with Bio Natural Cleaning Emulsion diluted at the rate of 50 ml in 5 Litres of warm water. Make sure that no moisture is allowed to remain on the waxed surface because it will cause staining.
INGREDIENTS	Beeswax, carnauba wax, earth/or paraffin wax, shellac wax, lemon peel oil, paraffin oils.
CLEANING	Use BIO Thinner.
COVERAGE	1 Litre covers approx. 20-50 sqm., depending on the absorbency of the wood, its surface conditions and the application method. On floor boards: Softwood 20 ml per sqm = approx. 50 sqm per Litre Hardwood 6-10 ml per sqm. = approx. 100 - 160 sqm
PACKAGING	BIO Antique Wax 175 ml and 1 Litre. BIO Hard Floor Wax 250 ml and 4 Litres.

PRECAUTION	Keep away from open flame and out of the reach of children. Please dispose used rags in a sealed metal container. Can spontaneously combust.
FIRST AID	Keep tightly sealed in a cool and dry place.

The preceding information is given as a general guide only. Some variations may occur or be advisable for particular conditions. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.

BIO Antique Wax & Hard Floor Wax is an environmentally friendly product.