

BIO NATURAL WOOD OIL & RED OIL

DESCRIPTION	These are penetrating and finishing oils designed to deepen and enhance the natural grain of timber. They give a matt or satin finish and can be used on any interior wooden surface, which is not subjected to heavy wear. Bio Red Oil contains a natural red plant dye, which reddens the timber surface and is deepening the natural tone and colour. Bio Natural Wood Oil and Bio Red Oil can be used as complete finishes, or in conjunction with other Bio products (see below). These oils should not be used on alkaline surfaces, plaster, concrete or fibro-cement. If considering use on other materials (such as brick, ceramic or cork), test-strips should be made to assess suitability.
PREPARATION	Surfaces should be well-sanded, dry and cleaned of greasy, waxy and dirty contaminants using BIO Thinner. Old coatings must be removed. Hardwoods and other timbers rich in natural oils, waxes, acids and terpenes should be degreased using BIO Thinner because these substances may mix with the oils and prolong its drying time.
APPLICATION	Brush, dip or spray BIO Oils working them well into the grain. Do not apply more oil than the surface can absorb. Remove excess oil with a dry, lint free cloth after approx. 15-30 minutes. Test the absorbency of the surface before application: for very absorbent timber, work in small areas otherwise the oil might dry before you are able to wipe off the excess, causing an uneven patchy finish. Drying time 24 hours. Do not use when temperature is below +10C and/or the relative humidity is above 80%; e.g.cold damp conditions, or when condensation, rain, dew or frost are likely to occur. Bio OILS may penetrate timber pores more easily if warmed to 60 +C. For matt finish apply one coat, for satin finish apply three coats. Repair and refinish by applying additional coats. Provide adequate ventilation during application and drying.
FINISHING	Bio oils can be used as complete finishes or they can be supplemented with: BIO All Purpose Varnish BIO Floor Varnish BIO Antique Wax BIO Japanese Seedlac - only after the oil has thoroughly dried and cured.
COVERAGE	1 Litre covers 8-12 sqm., depending on the absorbency of the timber.
CLEANING	Use <u>BIO Thinner</u> .
INGREDIENTS	Wood oil, linseed oil, lemon peel oil, paraffin oil, plant dye(red oil only).



Going Solar
60 Leicester St
Carlton VIC 3053
T 03 9348 1000
F 03 9348 0077
retail@goingsolar.com.au
www.goingsolar.com.au

20/05/2005

PACKAGING	BIO Wood Oil 1 Litre, 4 Litres and 20 Litres. BIO Red Oil 500 ml, 1 Litre, 4 Litres and 20 Litres.
PRECAUTION	Keep away from open flames and out of the reach of children. Please dispose of used rags in a sealed metal container. Can spontaneously combust.
STORAGE	Keep tightly sealed in a cool dry place.

Special precautions: Keep away from open flame and out of the reach of children. Do not misuse. Please dispose of used rags in a sealed metal container. Can spontaneously combust.

The preceding information is given as a general guide only. Some variations may occur or be advisable for particular conditions. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.

BIO Natural Wood Oil & Red Oil is an environmentally friendly product.