

BIO PRIMING OIL

DESCRIPTION	A penetrating oil for priming all absorbent interior surfaces, especially new wood, cork and unglazed stone tiles. Very suitable as a preliminary treatment under waxed, varnished or oiled finishes. For oiled finish see Bio Natural Wood Oil or Bio Teak Oil.
PREPARATION	All surface to be primed should be well sanded, dry and cleaned of greasy, waxy and dirty contaminants using <u>BIO Thinner</u> . Hardwoods and other timbers rich in natural oils, waxes, acids and terpenes should be degreased using Bio Thinner because these substances may mix with the Priming Oil and prolong its drying time. Old coatings must be removed.
APPLICATION	Can be brushed, rolled or sprayed. Do not apply more oil than the surface can absorb. Remove excess oil with a dry lint free cloth after approx. 15-30 minutes. Test the absorbency of the surface before application: for very absorbent timber, work in small areas otherwise the oil might dry before you are able to wipe off the excess, causing an uneven patchy finish. Do not use below 10 C and/or above 80% humidity, or when condensation, rain, dew or frost are likely to occur. Provide adequate ventilation during application and drying.
DRYING	Can be sanded after 24 hours, after which time treatment can continue. However, the oil takes up to 72 hours to dry completely.
COVERAGE	1 Litre covers approx. 10-12 sqm. Note: Coverage varies greatly with the absorbency of the material being primed. Cross-cut and other open-grained surfaces require considerably more oil.
CLEANING	Use <u>BIO Thinner</u> .
INGREDIENTS	Plant oils, essential oils and paraffin oil.
PACKAGING	1 and 4 Litres.
PRECAUTION	Keep away from open flames and out of the reach of children. Please dispose of used rags in a sealed metal container. Can spontaneously combust.
STORAGE	Keep tightly sealed in a cool and dry place. Surface skin may develop in opened cans.

The preceding information is given as a general guide only. Some variations may occur or be advisable for particular conditions. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.



20/05/2005

Going Solar
60 Leicester St
Carlton VIC 3053
T 03 9348 1000
F 03 9348 0077
retail@goingsolar.com.au
www.goingsolar.com.au

BIO Priming Oil is an environmentally friendly product.