

BIO WALL PRIMER INTERIOR

DESCRIPTION	A penetrating interior primer based on natural ingredients, for use with Bio Wall Paint. May be used on all surfaces such as plasterboard, concrete, fibro-cement, plaster and other absorbent crumbly surfaces.
PREPARATION	Prepare surface in accordance to AS 2311 The painting of buildings. Substrate should be dry and cleaned of greasy and dirty contaminants, and should be solid and resistant to pressure. Loose particles from crumbly surfaces must be brushed off. Old coats must be removed.
APPLICATION	Stir thoroughly with a broad flat stirrer before use. Apply evenly using a brush, roller or spray. Drying time is 2-6 hours, longer in cold and damp condition. Do not apply under 12+C.
INGREDIENTS	Water, lemon oil, borax, calcium carbonate, caolin, titanium dioxide, cellulose, surfactant, resins. castor oil, tspp,
CLEANING	Use warm, soapy water.
COVERAGE	1 Litre covers approx. 5-10 sqm depending on the absorbency of the substrate.
PACKAGING	1, 4 and 10 Litres.
PRECAUTION	Keep out of reach of children.
STORAGE	Keep tightly sealed in a cool and dry place.

The preceding information is given as a general guide only. Some variations may occur or be advisable for particular conditions. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.

BIO Wall Primer is an environmentally friendly product.