



Going Solar Pty Ltd
60L Leicester St Carlton VIC 3053
T: 03 9348 1000
W: www.goingsolar.com.au



• LOW ALLERGY
The natural base of BIO Products, allows your family to enjoy a better and healthier life-style.

- Our wall paint can be scrubbed clean and has a hiding power of 98.3%, which is better than most paints on the market. It has been tested by the Australian Defence Department Materials Testing Laboratory in September 1993 and meets the Australian Standard AS 1580.(Method of Paint Testing)
- **HEALTH AND ENVIRONMENT**
- By using Bio Products you are promoting the maintenance of a healthy balance between mankind and nature.



Coverage Chart

Each of our products has been extensively tested to ensure that it produces a high quality finish, but remember that this blend of ingredients is unique, therefore:

Please follow the application instructions carefully.

These traditionally made BIO Products should be applied in the traditional way.

Apply them thinly, which strengthens the bond between the wood and the product, and also shortens the drying time. You'll find that BIO drying times are longer than chemically-based products, because our organic natural products don't contain any poisonous drying agents (such as lead).

Always make certain that a coat is completely dry before further work on the surface.

Coverage	Approximately
Wall Paint	10 sqm per litre
Enamel Lacquers	8-12 sqm per litre
Wood Varnishes	
Coloured	10-12 sqm per litre
All Purpose	
Varnishes	12-15 sqm per litre
Floor Varnish	12-15 sqm per litre
Natural Wood Oil	8-12 sqm per litre
Red Oil	8-12 sqm per litre
Japanese Seedlac	10 sqm per litre
Antique Wax	40-50 sqm per litre
Hard Floor Wax	40-100 sqm per litre